



## Plug-in cabinets TANGO NEXT



**SLIMFIT** *Family*

### Product categories



### Technical features





<b>Lenght-Lunghezza</b> Longueur-Länge-Longitud mm		<b>1250 - 2P</b>	<b>1875 - 3P</b>	<b>2500 - 4P</b>
<b>TANGO NEXT</b>	<b>COMPACT</b>	■	■	■
	<b>NARROW</b>	■	■	■
<b>Dispaly area</b> Superficie di esposizione Warenpräsentationsfläche Surface d'exposition Superficie expositiva m2	<b>COMPACT</b>	1,9	2,86	3,81
	<b>NARROW</b>			
<b>Loading area</b> Superficie di appoggio Nutzfläche Surface de chargement Superficie de apoyo m2	<b>COMPACT</b>	0,96	1,44	1,86
	<b>NARROW</b>	1,13	1,66	2,19
<b>Net storage capacity</b> Capacità netta Nutzinhalt volume utile Capacitat neta dm3	<b>COMPACT</b>	674	1005	1345
	<b>NARROW</b>	875	1320	1750
<b>End thickness</b> Spessore spalla Stärke der Seitenwand Épaisseur de cheque joue Espesor lateral mm	30			





## Legend

 Meat	 Chicken	 Fish	 Pre-packed fish
 Delicatessen	 Cheese	 Dairy products	 Gastronomy
 Pastries	 Pre-packed fruit and vegetables	 Fruits and Vegetables	 Sandwiches
 Drinks	 Pizza	 Bread	 Frozen food and ice cream
 Off-cycle defrost	 Electric defrost	 Hot-gas defrosting system	 Manual defrost
 Ventilated	 Static	 Incorporated condensing unit	 Remote condensing unit
 Bagnomaria	 Ceramic glass	 Ice	 VSD Inverter technology
 LED lighting	 Zero C doors	 High efficiency fans	 R290 Propane refrigerant gas (R290)
 R134a R-134a - 400V/3PH/50Hz	 R404A R404A - 400V/3PH/50Hz	 R744 R744 - 400V/PH/50Hz	 Compressor hermetic reciprocating
 Hermetic scroll compressor	 Semi-hermetic reciprocating compressor	 VSD Inverter technology	 External installation
 Machinery room	 Soundproof housing	 On board condenser	 Remote condenser
 DUAL Medium & Low temperature	 Technokleen	 Thin Tech	 EB